## NSN 4820-00-177-5982

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-177-5982

Pipe Size Accommodated:
0.500 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
75.0 cubic feet per minute
Maximum Operating Temp:
-70.0 degrees fahrenheit 1st response450.0 degrees fahrenheit 2nd response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+60.0 to 140.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.500 inches 1st end
Opening Pressure Setting:
100.0 pounds per square inch
Special Features:
Pop-off type
Material:
Copper alloy
Media For Which Designed:
Ovugan, gangaja 2rd rannana
Oxygen, gaseous sid response
Oxygen, gaseous 3rd response  Style Designator:
Style Designator:
Style Designator: Straight thru
Style Designator:
Style Designator: Straight thru Thread Series Designator:
Style Designator: Straight thru Thread Series Designator: Npt 1st end
Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life:
Style Designator: Straight thru  Thread Series Designator: Npt 1st end Shelf Life: N/a

No

## NSN 4820-00-177-5982

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0