## NSN 4820-00-181-8912

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-181-8912 **Body Material:** Any acceptable **Body Style:** Straight thru Stem Material: Any acceptable Media For Which Designed: Water, fresh and water, salt **First End Connection Type:** Unthreaded internal pipe First End Style Designator: Streamlined with one brazing ring First End Pipe Size Accommodated: 1.250 inches Second End Relationship With First End: Identical **Seat Material:** Any acceptable **Packing Material:** Any acceptable Flow Control Device: Diaphragm Flow Control Device Material: Any acceptable **End Connection Quantity:** 2 Renewable Seat Ring Type: Threaded **Outlet Pressure Range:** +25.0 to 60.0 pounds per square inch **Regulation Type:** Automatic double stageautomatic double stage Valve Stem Design: Single seat **Valve Loading Method:** Spring **Maximum Inlet Pressure Rating:** 150.0 pounds per square inch

Not rated Filter:

Not included

**Outlet Pressure Accuracy Rating:** 

# NSN 4820-00-181-8912

Fluid Pressure Regulating Valve - Page 2 of 2



Tempurature Rating:
---------------------

165.0 degrees fahrenheit

**Special Features:** 

Ends w/o brazing rings installed

## **Special Test Features:**

High-impact shock tests are required as directed in paragraphs 3.6 and 4.4.2.3 of mil-v-2042

### **Test Data Document:**

81349-milv2042 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).81349-milv2042 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Or Standard:**

2 type2 type

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A21100