NSN 4820-00-181-9450

Stop-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-181-9450

Pipe Size Accommodated:
1.000 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Weight
Maximum Operating Temp:
775.0 degrees fahrenheit single response
Connection Style:
Socket (pipe) all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Special Features:
1.000 in. Valve size
Material:
Steel seat
Material Specification:
Mil-r-17131, mil-rcocr-a military specification single material response seat
Media For Which Designed:
Steam single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-s-901 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-v-22094 government specification
Specification Or Standard:
D composition
Shelf Life:

N/a

NSN 4820-00-181-9450

Stop-check Valve - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-r-17131 spec.