

View Online at <https://aerobasegroup.com/nsn/4820-00-183-6995>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) all ends

Valve Operation Method:

Automatic or manual

Connection Type:

Threaded external pipe all ends

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

2.000 inches all ends

Material:

Nickel alloy flow control device

Material Specification:

Qq-c-390, alloy d4 federal specification single material response body

Media For Which Designed:

Steam single response

Style Designator:

Straight thru

Test Data Document:

03950-cid88207229 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0