## NSN 4820-00-185-6879

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-185-6879 **Thread Direction:** Right-hand all ends **Flow Control Device: Poppet Disk Loading Method:** Spring Valve Discharge Flow Rate: 10.0 gallons per minute **Renewable Seat Ring Type:** Pressed-in **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe all ends **Features Provided:** Pressure tight outlet side **Adjustable Pressure Range:** +900.0/+2000.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.250 inches all ends **Special Features:** Includes one alloy pipe plug for unused side port, 0.250 inch npt thd size Material: Steel flow control device Media For Which Designed: Straight through note: to be used for valve bodies of separable sections.

Water-oil-gas single response **Surface Treatment:** Cadmium **Style Designator: Thread Series Designator:** Npt all ends Shelf Life: N/a **Unit Of Measure:** 

## NSN 4820-00-185-6879

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0