

View Online at <https://aerobasegroup.com/nsn/4820-00-186-3829>

Pipe Size Accommodated:

0.750 inches all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

150.0 degrees fahrenheit single response

Connection Style:

Socket with brazing ring (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Unthreaded internal pipe all ends

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Maximum Operating Pressure:

400.0 pounds per square inch single response

Special Features:

0.750 in. Valve size, ea valve shall have three buna-n o-rings packed in a bag and securely attached with instructions, o-rings for oil service only

Material:

Plastic polychlorotrifluoroethylene flow control device

Material Specification:

Qq-c-390, alloy d4 federal specification single material response body

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight thru

Test Data Document:

03950-cid882037167 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A530b0