

View Online at <https://aerobasegroup.com/nsn/4820-00-187-6698>

Offset Distance:

2.250 inches

Flow Control Device:

Poppet

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Valve Operation Method:

Manual

Flange Shape:

Round 1st end

Connection Type:

Flange 1st end

Mounting Position:

Horizontal

Features Provided:

Bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Criticality Code Justification:

Zzzy

Outside Diameter:

6.125 inches 1st end

Face To Face Distance:

12.000 inches

Thickness:

0.875 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

2.875 inches 1st end

Material:

Nickel alloy 400 stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Straight through w/offset flanged ends

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A530b0