

View Online at <https://aerobasegroup.com/nsn/4820-00-188-8263>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

8 all ends

**Maximum Operating Temp:**

425.0 degrees fahrenheit single response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Mounting Position:**

Horizontal

**Valve Size:**

4.000 inches

**Maximum Operating Pressure:**

100.0 pounds per square inch single response

**Outside Diameter:**

7.687 inches all ends

**Face To Face Distance:**

12.500 inches

**Thickness:**

0.500 inches all ends

**Bolt Hole Diameter:**

0.562 inches all ends

**Bolt Circle Diameter:**

6.562 inches all ends

**Flange Face Design:**

Plain all ends

**Special Features:**

Valve size 4.000 in.

**Material:**

Nickel alloy flow control device

**Material Specification:**

Qq-n-288, comp b federal specification single material response stem

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Straight through flanged ends

**Test Data Document:**

03950-cid882033194 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 80064-5000-s4824-c1385541 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530b0