## NSN 4820-00-191-3810

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-191-3810

Poppet
Disk Loading Method:
Spring
Bolt Hole Quantity:
2 1st end
Width:
1.300 inches 1st end
Length:
2.500 inches 1st end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+5.5/+6.5 pounds per square inch
Thickness:
0.125 inches 1st end
Bolt Hole Diameter:
0.185 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.830 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
0.960 inches 1st end
Flange Face Design:
Plain 1st end
Special Features:
2 mtg slots one end 0.185 in. W, 0.960 in. Apart c-to-c
Material:
Stainless steel body
Media For Which Designed:
Air single response
Style Designator:
Straight through note: to be used for valve bodies of separable sections.
Furnished Items And Quantity:
1 cap and 1 spring and 1 washer
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-00-191-3810

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0