## NSN 4820-00-191-6881

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-191-6881

**Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Valve Discharge Flow Rate:** 200.0 cubic feet per minute **Maximum Operating Temp:** 450.0 degrees fahrenheit single response **Connection Style:** External seat for gasket seal (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss 1st end **Features Provided:** Valve stem lock shield and pressure tight outlet side Thready Qty Per Inch (tpi): 12 1st end **Adjustable Pressure Range:** +47.0/+53.0 pounds per square inch **Maximum Operating Pressure:** 60.0 pounds per square inch single response **Thread Size:** 1.312 inches 1st end **Opening Pressure Setting:** 50.0 pounds per square inch **Outside Diameter Tube Accommodated:** 1.000 inches 1st end Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, alloy2024 federal specification all material responses Media For Which Designed: Air single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response

Style Designator:

Straight thru

## NSN 4820-00-191-6881

Safety Relief Valve - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0
Mil-std (military Standard):

Mil-a-8625 spec.