

View Online at <https://aerobasegroup.com/nsn/4820-00-192-9438>

**Flow Control Device:**

Disk

**Bonnet Type:**

Exposed spring

**Bonnet Attachment Method:**

Bolted

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

21000.0 pounds per hour

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

8 1st end

**Valve Operation Method:**

Automatic or manual

**Flange Shape:**

Round with holes 2nd end

**Connection Type:**

Flange 2nd end

**Features Provided:**

Pressure tight outlet side

**Adjustable Pressure Range:**

+1272.0/+1428.0 pounds per square inch

**Opening Pressure Setting:**

1375.0 pounds per square inch

**Outside Diameter:**

7.562 inches 1st end

**Bolt Hole Diameter:**

1.062 inches 2nd end

**Bolt Circle Diameter:**

6.000 inches 1st end

**Flange Face Design:**

Plain 2nd end

**Special Features:**

The end connection identified above as the second end is the valve inlet

**Style Designator:**

Angle

**Reference Number Differentiating Characteristics:**

As differentiated by the valve discharge flow rate requirement

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0