NSN 4820-00-192-9438

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-192-9438

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

21000.0 pounds per hour

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 2nd end

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+1272.0/+1428.0 pounds per square inch

Opening Pressure Setting:

1375.0 pounds per square inch

Outside Diameter:

7.562 inches 1st end

Bolt Hole Diameter:

1.062 inches 2nd end

Bolt Circle Diameter:

6.000 inches 1st end

Flange Face Design:

Plain 2nd end

Special Features:

The end connection identified above as the second end is the valve inlet

Style Designator:

Angle

Reference Number Differentiating Characteristics:

As differentiated by the valve discharge flow rate requirement

Shelf Life:

N/a

NSN 4820-00-192-9438

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

