NSN 4820-00-198-2344

Safety Relief Valve - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/4820-00-198-2344

Pipe Size Accommodated:
0.125 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
280.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+2.0/+6.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.125 inches 1st end
Opening Pressure Setting:
4.0 pounds per square inch
Material:
Aluminum alloy 2024 body
Material Specification:
Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:

NSN 4820-00-198-2344

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0