NSN 4820-00-198-2344

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-198-2344

Pipe Size Accommodated:

0.125 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

280.0 degrees fahrenheit single response

Connection Style:

Plain (pipe) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external pipe 1st end

Adjustable Pressure Range:

+2.0/+6.0 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.125 inches 1st end

Opening Pressure Setting:

4.0 pounds per square inch

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6, alloy2024, t4 federal specification 1st material response flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4820-00-198-2344

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

