## NSN 4820-00-202-5538

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-202-5538

Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3000.0 pounds per hour
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3800.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
3450.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:
Air single response
Style Designator:
00 110
Straight thru
Thread Series Designator:
Thread Series Designator:

## NSN 4820-00-202-5538

Safety Relief Valve - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A046b0