## NSN 4820-00-202-5806

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-202-5806

Thread	Class:

3a all ends

**Thread Direction:** 

Right-hand all ends

## Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

180.0 degrees fahrenheit 2nd response

#### **Connection Style:**

Flared (tube) all ends

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded external tube all ends

**Mounting Position:** 

Horizontal

## Maximum Operating Pressure:

600.0 pounds per square inch single response

## Thread Size:

0.750 inches all ends

## Seat Angle:

37.0 degrees all ends

#### **Outside Diameter Tube Accommodated:**

0.500 inches all ends

## Material:

Aluminum alloy 2024 body

#### Material Specification:

Qq-a-225/6, alloy 2024, t4 federal specification single material response seat

#### Media For Which Designed:

Fuel/oil, hydrocarbon 2nd response

#### Surface Treatment:

Anodize

#### Style Designator:

Straight thru

#### **Thread Series Designator:**

Unjf all ends

Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-00-202-5806

Check Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A530b0

