## NSN 4820-00-202-6544

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-202-6544

Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
50600.0 pounds per hour
Renewable Seat Ring Type:
Threaded
<b>Bolt Hole Quantity:</b>
9 2nd end
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Valve Size:
2.500 inches
Opening Pressure Setting:
1355.0 pounds per square inch
Outside Diameter:
9.625 inches 1st end
<b>Bolt Hole Diameter:</b>
1.062 inches 1st end
<b>Bolt Circle Diameter:</b>
7.688 inches 2nd end
Flange Face Design:
Plain 2nd end
Raised Face Diameter:
6.375 inches 1st end
Style Designator:
Angle flanged ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4820-00-202-6544

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0