NSN 4820-00-202-6638

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-202-6638

Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Union **Disk Loading Method:** Spring **Renewable Seat Ring Type:** Welded **Bolt Hole Quantity:** 6 all ends Valve Operation Method: Automatic or manual Flange Shape: Round with holes all ends **Connection Type:** Flange all ends Valve Size: 2.000 inches Adjustable Pressure Range: +18.0/+32.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch single response **Outside Diameter:** 5.562 inches all ends Thickness: 0.438 inches all ends **First Connection Face To Centerline Distance:** 4.750 inches **Bolt Hole Diameter:** 0.562 inches all ends **Second Connection Face To Centerline Distance:** 5.250 inches **Bolt Circle Diameter:** 4.438 inches all ends Flange Face Design: Plain all ends Material: Nickel alloy r-405 stem or copper alloy 462 stem **Material Specification:**

Qq-n-281 cl b federal specification 1st material response stem or mil-b-994 cl d military specification 2nd material response stem

NSN 4820-00-202-6638

Safety Relief Valve - Page 2 of 2



Media For Which Designed:

Water, salt 1st response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-b-16541 spec.