NSN 4820-00-202-6822

Stop-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-00-202-6822

Inside screw
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
6 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal or vertical
Valve Size:
1.500 inches
Maximum Operating Pressure:
500.0 pounds per square inch single response
Outside Diameter:
5.062 inches 1st end
Face To Face Distance:
10.250 inches
Thickness:
0.812 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
3.938 inches 1st end
Flange Face Design:
Plain 1st end
Extra Long Reference Number:
4824-3132361revdpc1-4-6t08-11-1-00
Material:
Nickel alloy 400 stem or nickel alloy r-405 stem
Media For Which Designed:
Water, salt single response
Style Designator:

Straight through flanged ends

NSN 4820-00-202-6822

Stop-check Valve - Page 2 of 2



Reference Number Differentiating Characteristics:	
Drawing no.	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

Yes - demil/mli

Fiig:

A530b0