NSN 4820-00-202-7130

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-202-7130

| Flow Control Devices |
|--|
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Outside screw-yoke |
| Bonnet Attachment Method: |
| Bolted |
| Renewable Seat Ring Type: |
| Threaded Secretifies |
| Bolt Hole Quantity: |
| 4 1st end |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Flange 1st end |
| Features Provided: |
| Bonnet packing |
| Valve Size: |
| 0.500 inches |
| Outside Diameter: |
| 4.000 inches 1st end |
| Face To Face Distance: |
| 7.000 inches |
| Thickness: |
| 0.688 inches 1st end |
| Bolt Hole Diameter: |
| 0.562 inches 1st end |
| Bolt Circle Diameter: |
| 2.875 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Material: |
| Copper alloy 922 seat or copper alloy 903 seat |
| Style Designator: |
| Straight through flanged ends |
| Reference Number Differentiating Characteristics: |
| As differentiated by the material requirements for the disk, seat and stem |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-00-202-7130

Globe Valve - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A046b0