

View Online at <https://aerobasegroup.com/nsn/4820-00-202-7164>

**Flow Control Device:**

Disk

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

9 all ends

**Maximum Operating Temp:**

425.0 degrees fahrenheit 1st response

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes all ends

**Connection Type:**

Flange all ends

**Features Provided:**

Bonnet packing

**Valve Size:**

4.000 inches

**Maximum Operating Pressure:**

400.0 pounds per square inch single response

**Outside Diameter:**

9.250 inches all ends

**Face To Face Distance:**

15.000 inches

**Thickness:**

1.000 inches all ends

**Bolt Hole Diameter:**

0.812 inches all ends

**Bolt Circle Diameter:**

7.688 inches all ends

**Flange Face Design:**

Plain all ends

**Material:**

Copper alloy 922 seat or copper alloy 903 seat

**Material Specification:**

Qq-c-465 federal specification single material response stem

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight through flanged ends

**Reference Number Differentiating Characteristics:**

As differentiated by seat material, stem material, flow control device material

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0