NSN 4820-00-202-8176

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-202-8176

Pipe Size Accommodated:
0.500 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing
Thready Qty Per Inch (tpi):
14 1st end
Maximum Operating Pressure:
Maximum Operating Pressure: 300.0 pounds per square inch 2nd response
· · · ·
300.0 pounds per square inch 2nd response
300.0 pounds per square inch 2nd response Thread Size:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure:
300.0 pounds per square inch 2nd response Thread Size: 0.500 inches 1st end Material: Plastic flow control device or rubber flow control device Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Thread Series Designator: Npt 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: