

View Online at <https://aerobasegroup.com/nsn/4820-00-202-8261>

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

3 2nd end

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Facility:

Bracket

Features Provided:

Pressure tight outlet side

Valve Size:

0.500 inches

Adjustable Pressure Range:

+678.0/+820.0 pounds per square inch

Maximum Operating Pressure:

750.0 pounds per square inch single response

Outside Diameter:

3.750 inches 1st end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

3.250 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

3.125 inches

Bolt Circle Diameter:

2.625 inches 1st end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

2.000 inches 1st end

Material:

Stainless steel stem

Material Specification:

Qq-s-763 federal specification single material response stem

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-s-15083 spec.