## NSN 4820-00-202-8261

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Attachment Method:** 

**Disk Loading Method:** 

Bonnet Type: Inside spring

Disk

Union



View Online at https://aerobasegroup.com/nsn/4820-00-202-8261

Spring
Bolt Hole Quantity:
3 2nd end
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Mounting Facility:
Bracket
Features Provided:
Pressure tight outlet side
Valve Size:
0.500 inches
Adjustable Pressure Range:
+678.0/+820.0 pounds per square inch
Maximum Operating Pressure:
750.0 pounds per square inch single response
Outside Diameter:
3.750 inches 1st end
Thickness:
0.562 inches 1st end
First Connection Face To Centerline Distance:
3.250 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.125 inches
Bolt Circle Diameter:
2.625 inches 1st end
Flange Face Design:
Plain 2nd end

## NSN 4820-00-202-8261

Safety Relief Valve - Page 2 of 2



Raised Face Height:
0.250 inches 1st end
Raised Face Diameter:
2.000 inches 1st end
Material:
Stainless steel stem
Material Specification:
Qq-s-763 federal specification single material response stem
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Angle flanged ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0
Mil-std (military Standard):
Mil-s-15083 spec.