NSN 4820-00-203-0068

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-203-0068

| Pipe Size Accommodated: |
|---|
| 1.000 inches 2nd end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 366.0 degrees fahrenheit single response |
| Connection Style: |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Bonnet packing and pressure tight outlet side |
| Adjustable Pressure Range: |
| +5.0/+25.0 pounds per square inch |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Thread Size: |
| 1.000 inches 2nd end |
| Material: |
| Steel stem |
| Media For Which Designed: |
| Steam single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4820-00-203-0068

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0