## NSN 4820-00-203-2589

Safety Relief Valve - Page 1 of 2

**Flow Control Device:** 

**Bonnet Type:** 

Disk

View Online at https://aerobasegroup.com/nsn/4820-00-203-2589



Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Bolt Hole Quantity:** 4 all ends Maximum Operating Temp: 650.0 degrees fahrenheit single response Valve Operation Method: Manual or automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Features Provided:** Valve stem lock shield Adjustable Pressure Range: +101.0/+149.0 pounds per square inch Maximum Operating Pressure: 150.0 pounds per square inch single response **Outside Diameter:** 4.250 inches all ends Thickness: 0.438 inches all ends **Bolt Hole Diameter:** 0.562 inches all ends **Bolt Circle Diameter:** 3.125 inches all ends Flange Face Design: Plain all ends Material: Stainless steel stem Media For Which Designed: Steam single response Style Designator: Angle Shelf Life: N/a

## NSN 4820-00-203-2589

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

