NSN 4820-00-203-2589



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-203-2589 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Bolt Hole Quantity:** 4 all ends **Maximum Operating Temp:** 650.0 degrees fahrenheit single response **Valve Operation Method:** Manual or automatic Flange Shape: Round with holes all ends **Connection Type:** Flange all ends **Features Provided:** Valve stem lock shield **Adjustable Pressure Range:** +101.0/+149.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Outside Diameter:** 4.250 inches all ends Thickness: 0.438 inches all ends **Bolt Hole Diameter:** 0.562 inches all ends **Bolt Circle Diameter:** 3.125 inches all ends Flange Face Design: Plain all ends Material: Stainless steel stem Media For Which Designed: Steam single response **Style Designator:**

Angle

Shelf Life:

N/a

NSN 4820-00-203-2589

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0