## NSN 4820-00-203-7575

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-203-7575

Pipe Size Accommodated:							
0.250 inches 1st end							
Thread Direction:							
Right-hand 1st end							
Flow Control Device:							
Disk							
Bonnet Type:							
Inside spring							
Bonnet Attachment Method:							
Threaded							
Disk Loading Method:							
Spring							
Valve Discharge Flow Rate:							
23.0 cubic feet per minute							
Maximum Operating Temp:							
250.0 degrees fahrenheit single response							
End Application:							
Grumman a10 aircraft							
Connection Style:							
Plain (pipe) 1st end							
Valve Operation Method:							
Automatic or manual							
Connection Type:							
Threaded external pipe 1st end							
Features Provided:							
Valve stem lock shield							
Maximum Operating Pressure:							
300.0 pounds per square inch single response							
Thread Size:							
0.250 inches 1st end							
Opening Pressure Setting:							
70.0 pounds per square inch							
Material:							
Stainless steel flow control device							
Media For Which Designed:							
Air single response							
Style Designator:							
Angle							
Thread Series Designator:							
Npt 1st end							
Shelf Life:							
N/a							

## NSN 4820-00-203-7575

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0