

View Online at <https://aerobasegroup.com/nsn/4820-00-203-7911>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 all ends

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Valve stem lock shield and pressure tight outlet side

Valve Size:

3.000 inches

Adjustable Pressure Range:

+5.0/+10.0 pounds per square inch

Outside Diameter:

6.625 inches all ends

Thickness:

0.562 inches all ends

First Connection Face To Centerline Distance:

5.500 inches

Bolt Hole Diameter:

0.562 inches all ends

Second Connection Face To Centerline Distance:

6.250 inches

Bolt Circle Diameter:

5.500 inches all ends

Flange Face Design:

Plain all ends

Material:

Copper alloy body

Media For Which Designed:

Water, fresh single response

Style Designator:

Angle flanged ends

Furnished Items And Quantity:

1 lever

Specification Data:

81349-mil-v-24332 government specification

Specification Or Standard:

A grade or b grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.