

View Online at <https://aerobasegroup.com/nsn/4820-00-203-8030>

Pipe Size Accommodated:

1.500 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

4 2nd end

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Automatic or manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Valve stem lock shield

Thready Qty Per Inch (tpi):

11-1/2 1st end

Adjustable Pressure Range:

+7.0/+25.0 pounds per square inch

Maximum Operating Pressure:

100.0 pounds per square inch single response

Thread Size:

1.500 inches 1st end

Outside Diameter:

4.500 inches 2nd end

Thickness:

0.438 inches 2nd end

First Connection Face To Centerline Distance:

3.062 inches

Bolt Hole Diameter:

0.562 inches 2nd end

Second Connection Face To Centerline Distance:

2.188 inches

Bolt Circle Diameter:

3.375 inches 2nd end

Flange Face Design:

Plain 2nd end

Special Features:

Bolt holes in flange to straddle centerlines

Material:

Nickel alloy flow control device

Media For Which Designed:

Steam single response

Style Designator:

Angle flanged ends

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0