## NSN 4820-00-204-1955

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-204-1955 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded internal boss all ends **Mounting Facility:** Threaded fastener **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends **Outside Diameter Tube Accommodated:** 0.500 inches all ends Material: Steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Supplementary Features:** Optional flow control device: stem **Thread Series Designator:** Unf all ends

Shelf Life:

N/a

## NSN 4820-00-204-1955

Lift-check Valve - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A530b0