NSN 4820-00-208-7109

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-208-7109

Thread Class:

3a 1st end

Right-hand 1st end

Flow Control Device:

ъ .

Thread Direction:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

280.0 degrees fahrenheit single response

Connection Style:

Plain (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Adjustable Pressure Range:

+0.5/+2.5 pounds per square inch

Maximum Operating Pressure:

200.0 pounds per square inch single response

Thread Size:

0.437 inches 1st end

Opening Pressure Setting:

1.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Steel comp 303

Material Specification:

66 federal standard single material response

Media For Which Designed:

Nitrogen, gaseous 5th response

Style Designator:

Straight thru

Thread Series Designator:

Unjf 1st end

Furnished Items And Quantity:

1 deflector cap

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-00-208-7109

Safety Relief Valve - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A046b0