NSN 4820-00-211-4783

Shuttle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-211-4783 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Piston Valve Discharge Flow Rate: 9.0 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Reduced gasket seal err-100 **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 3rd end Thready Qty Per Inch (tpi): 18 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end Seat Angle: 37.0 degrees 1st end **Center To Center Distance:** 2.438 inches **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Tee w/offset **Thread Series Designator:** Unjf 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-00-211-4783 Shuttle Valve - Page 2 of 2



Fiig:

A046b0