## NSN 4820-00-211-4783

Shuttle Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-211-4783

### Thread Class:

3b 1st end

**Thread Direction:** 

Right-hand 1st end

#### Flow Control Device:

Piston

#### Valve Discharge Flow Rate:

9.0 gallons per minute

#### Maximum Operating Temp:

160.0 degrees fahrenheit single response

#### **Connection Style:**

Reduced gasket seal err-100

#### Valve Operation Method:

Automatic

#### **Connection Type:**

Threaded internal boss 3rd end

#### Thready Qty Per Inch (tpi):

18 1st end

#### Maximum Operating Pressure:

3000.0 pounds per square inch single response

#### Thread Size:

0.562 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### **Center To Center Distance:**

2.438 inches

#### **Outside Diameter Tube Accommodated:**

0.375 inches 1st end

#### Material:

Stainless steel flow control device

#### Media For Which Designed:

Hydraulic fluid, phosphate-ester base single response

#### Style Designator:

Tee w/offset

#### **Thread Series Designator:**

Unjf 1st end

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# **NSN 4820-00-211-4783** Shuttle Valve - Page 2 of 2

Fiig: A046b0

