NSN 4820-00-214-0173

Stop-check Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-00-214-0173

Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
16 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Valve Size:
12.000 inches
Maximum Operating Pressure:
50.0 pounds per square inch single response
Outside Diameter:
16.562 inches 1st end
Thickness:
0.688 inches 1st end
First Connection Face To Centerline Distance:
13.375 inches
Bolt Hole Diameter:
0.812 inches 1st end
Second Connection Face To Centerline Distance:
13.375 inches
Bolt Circle Diameter:
15.000 inches 1st end
Flange Face Design:
Plain 1st end
Special Features:
Left hand lever assembly
Media For Which Designed:

Water, salt single response

NSN 4820-00-214-0173

Stop-check Valve - Page 2 of 2



STV/IA	LIDEIA	natari
SIVIE	Desig	naioi.

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0