NSN 4820-00-215-7873

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-215-7873

Pipe Size Accommodated:
0.375 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Piston
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3.0 gallons per minute
Renewable Seat Ring Type:
Pressed-in
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+500.0/+2500.0 pounds per square inch
Maximum Operating Pressure:
2500.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Opening Pressure Setting:
1500.0 pounds per square inch
Special Features:
W/screw adjustment for relief pressure setting
Material:
Steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Cross
Thread Series Designator:
Nptf all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-215-7873

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0