

View Online at <https://aerobasegroup.com/nsn/4820-00-220-1792>

**Thread Class:**

3a all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

225.0 degrees fahrenheit 2nd response

**Connection Style:**

Flared (tube) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch 2nd response

**Thread Size:**

0.562 inches all ends

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.3750 inches 1st end

**Special Features:**

30.0 psi valve opening pressure

**Material:**

Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device and steel comp 303 flow control device

**Material Specification:**

66 federal standard 1st material response flow control device and mil-g-1149, type 2, cl 5 military specification 2nd material response flow control device and 66 federal standard 3rd material response flow control device

**Media For Which Designed:**

Oil, hydraulic 2nd response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Straight thru

**Thread Series Designator:**

Unf all ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A530b0

**Mil-std (military Standard):**

Mil-g-1149 spec.