

View Online at <https://aerobasegroup.com/nsn/4820-00-220-1850>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

13000.0 pounds per hour

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 1st end

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Features Provided:

Pressure tight outlet side

Adjustable Pressure Range:

+580.0/+630.0 pounds per square inch

Opening Pressure Setting:

624.0 pounds per square inch

Outside Diameter:

6.500 inches 2nd end

Thickness:

1.000 inches 1st end

Bolt Hole Diameter:

0.688 inches 2nd end

Bolt Circle Diameter:

5.188 inches 2nd end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

3.625 inches 1st end

Style Designator:

Angle

Reference Number Differentiating Characteristics:

As differentiated by the valve discharge flow rate requirement

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0