NSN 4820-00-220-1856

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-220-1856 **Thread Class:** 3b 2nd end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 400.0 degrees fahrenheit single response **Connection Style:** Gasket seal (boss) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Mounting Position:** Horizontal or vertical Thready Qty Per Inch (tpi): 12 2nd end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.312 inches 2nd end Seat Angle: 37.0 degrees 1st end **Outside Diameter Tube Accommodated:** 1.000 inches 2nd end **Special Features:** 10.0 psi valve opening pressure Material: Aluminum alloy body Media For Which Designed: Water-oil-gas single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:**

Thread Series Designate
Unj 2nd end

NSN 4820-00-220-1856

Check Valve - Page 2 of 2



Shelf	Life:
Onch	LIIC.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.