

View Online at <https://aerobasegroup.com/nsn/4820-00-220-3918>

Pipe Size Accommodated:

0.125 inches 2nd end

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Maximum Operating Temp:

180.0 degrees fahrenheit 2nd response

Connection Style:

Plain (pipe) 2nd end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thread Size:

0.437 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Special Features:

2.0 psi valve opening pressure

Material:

Steel comp 304 flow control device and rubber butadiene-acrylonitrile class nbr flow control device and steel comp 303 flow control device

Material Specification:

66 federal standard single material response body

Media For Which Designed:

Alcohol, ethyl 1st response

Surface Treatment:

Passivate

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-p-5315 spec.