NSN 4820-00-223-0149

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-223-0149

| Thread Olean | | | | | |
|--|--|--|--|--|--|
| Thread Class: | | | | | |
| 3a all ends | | | | | |
| Thread Direction: | | | | | |
| Right-hand all ends | | | | | |
| Flow Control Device: | | | | | |
| Poppet | | | | | |
| Disk Loading Method: | | | | | |
| Spring | | | | | |
| Maximum Operating Temp: | | | | | |
| 275.0 degrees fahrenheit single response | | | | | |
| Connection Style: | | | | | |
| Flareless all ends | | | | | |
| Valve Operation Method: | | | | | |
| Automatic | | | | | |
| Connection Type: | | | | | |
| Threaded external tube all ends | | | | | |
| Mounting Position: | | | | | |
| Horizontal or vertical | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 12 all ends | | | | | |
| Maximum Operating Pressure: | | | | | |
| 3000.0 pounds per square inch single response | | | | | |
| Thread Size: | | | | | |
| 1.062 inches all ends | | | | | |
| Seat Angle: | | | | | |
| 12.0 degrees 1st end | | | | | |
| Opening Pressure Setting: | | | | | |
| 10.0 pounds per square inch | | | | | |
| Special Features: | | | | | |
| Second or outlet end bulkhead type | | | | | |
| Material: | | | | | |
| Steel comp 630 seat | | | | | |
| Material Specification: | | | | | |
| Qq-s-763, cl 440c federal specification single material response flow control device | | | | | |
| Media For Which Designed: | | | | | |
| Oil, hydraulic single response | | | | | |
| Surface Treatment: | | | | | |
| Passivate | | | | | |
| Surface Treatment Specification: | | | | | |
| Qq-p-35 federal specification single treatment response | | | | | |
| Style Designator: | | | | | |

Straight thru

NSN 4820-00-223-0149

Check Valve - Page 2 of 2



| _ | | • | _ | |
|---|-------|---------|-------------|-----------|
| ı | hread | Series | 1)66 | ignator: |
| • | mcaa | OCI ICS | D C3 | igilatoi. |

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0