NSN 4820-00-223-0149

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-223-0149

Thread Olean					
Thread Class:					
3a all ends					
Thread Direction:					
Right-hand all ends					
Flow Control Device:					
Poppet					
Disk Loading Method:					
Spring					
Maximum Operating Temp:					
275.0 degrees fahrenheit single response					
Connection Style:					
Flareless all ends					
Valve Operation Method:					
Automatic					
Connection Type:					
Threaded external tube all ends					
Mounting Position:					
Horizontal or vertical					
Thready Qty Per Inch (tpi):					
12 all ends					
Maximum Operating Pressure:					
3000.0 pounds per square inch single response					
Thread Size:					
1.062 inches all ends					
Seat Angle:					
12.0 degrees 1st end					
Opening Pressure Setting:					
10.0 pounds per square inch					
Special Features:					
Second or outlet end bulkhead type					
Material:					
Steel comp 630 seat					
Material Specification:					
Qq-s-763, cl 440c federal specification single material response flow control device					
Media For Which Designed:					
Oil, hydraulic single response					
Surface Treatment:					
Passivate					
Surface Treatment Specification:					
Qq-p-35 federal specification single treatment response					
Style Designator:					

Straight thru

NSN 4820-00-223-0149

Check Valve - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0