NSN 4820-00-223-3414

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-223-3414

•
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
14 2nd end
Adjustable Pressure Range:
+5.0/+250.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
75.0 pounds per square inch
Special Features:
Stem point casehardened
Material:
Copper alloy body
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end

NSN 4820-00-223-3414

Safety Relief Valve - Page 2 of 2



_			-		
C	hο	14		.ife	•
•			_	.116	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0