NSN 4820-00-223-3414

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-223-3414

Pipe Size Accommodated:

0.750 inches 2nd end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Maximum Operating Temp:

406.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) 1st end

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

14 2nd end

Adjustable Pressure Range:

+5.0/+250.0 pounds per square inch

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Opening Pressure Setting:

75.0 pounds per square inch

Special Features:

Stem point casehardened

Material:

Copper alloy body

Media For Which Designed:

Water, fresh single response

Style Designator:

Angle

Thread Series Designator:

Npt 1st end

NSN 4820-00-223-3414

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

