## NSN 4820-00-224-7644

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-224-7644

Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
275.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 2nd end
Mounting Position:
Horizontal or vertical
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Material:
Steel comp 316 seat
Material Specification:
Qq-s-763, class 440 c federal specification 1st material response flow control device
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-s-5002 military specification single treatment response
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-224-7644

Check Valve - Page 2 of 2



Fiig:

A530b0

Mil-std (military Standard):

Mil-s-5002 spec.