

View Online at <https://aerobasegroup.com/nsn/4820-00-225-2413>

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Bolt Hole Quantity:

6 1st end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

11-1/2 2nd end

Maximum Operating Pressure:

250.0 pounds per square inch single response

Thread Size:

1.500 inches 2nd end

Criticality Code Justification:

Zzzy

Outside Diameter:

5.062 inches 1st end

Thickness:

0.812 inches 1st end

Bolt Hole Diameter:

0.562 inches 1st end

Bolt Circle Diameter:

3.938 inches 1st end

Flange Face Design:

Plain 1st end

Material:

Nickel alloy 400 stem

Media For Which Designed:

Water, salt single response

Style Designator:

Straight thru

Thread Series Designator:

Npsh 2nd end

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A046b0