NSN 4820-00-225-7186

Safety Relief Valve - Page 1 of 2

Thread Class: 3a all ends



View Online at https://aerobasegroup.com/nsn/4820-00-225-7186

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3.5 gallons per minute
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Seat Angle:
37.0 degrees all ends
Opening Pressure Setting:
2800.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Material:
Stainless steel stem
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Err-090
Thread Series Designator:
Unf all ends
Shelf Life:
N/a
Unit Of Measure:

NSN 4820-00-225-7186

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0