NSN 4820-00-225-7186

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-225-7186

Tł	nread	Class:
_		

3a all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.5 gallons per minute

Connection Style:

Gasket sea (boss) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss all ends

Features Provided:

Pressure tight outlet side

Thready Qty Per Inch (tpi):

18 all ends

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.562 inches all ends

Seat Angle:

37.0 degrees all ends

Opening Pressure Setting:

2800.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches all ends

Material:

Stainless steel stem

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Style Designator:

Err-090

Thread Series Designator:

Unf all ends

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-225-7186

Safety Relief Valve - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A046b0

