NSN 4820-00-228-2876

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-228-2876

Pipe Size Accommodated:
0.375 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+300.0/+4000.0 pounds per square inch
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Opening Pressure Setting:
4000.0 pounds per square inch
Special Features:
Can be reset to any desired cracking pressure after installation
Material:
Stainless steel seat
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-228-2876

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0