NSN 4820-00-229-2998

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-229-2998

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3.0 cubic feet per minute
Maximum Operating Temp:
125.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield and pressure tight outlet side
Adjustable Pressure Range:
+55.0/+200.0 pounds per square inch
Maximum Operating Pressure:
155.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
155.0 pounds per square inch
Material:
Silicon flow control device
Media For Which Designed:
Air single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-229-2998

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0